



Integrated Messaging Solutions

Integrated messaging solutions automate your message delivery so your customers can get the responsive, professional support they deserve. The system records messages automatically, keeping you in touch 24-hours a day. And of course, you'll love the cost savings. Panasonic messaging combine convenience with cost-savings all while producing a more satisfied customer.

Email Integration and Voice Mail with Auto Attendant

Add a KX-TVA series voice processing system and easily manage calls using the built-in automated attendant service, voice mail with email integration, and more. With the high level of integration between the TVA and the TDE600, you can enjoy features like voice mail LCD menus that allow you to access and manage your voice mailbox using the LCD display and soft keys. With so many choices, it's easy to custom design a system that's right for you.

MAXIMUM CO LINES				
Type	Base Unit	Base Unit +1 Expansion Shelf	Base Unit +2 Expansion Shelves	Base Unit +3 Expansion Shelves
Total Number of CO Lines	192	352	512	640
CO Line (Physical CO Line Card)	160	320	480	640
CO Line (Virtual CO Line Card)	32			

MAXIMUM TERMINAL EQUIPMENT				
Type	Base Unit	Base Unit +1 Expansion Shelf	Base Unit +2 Expansion Shelves	Base Unit +3 Expansion Shelves
Telephone (using Digital Extra Device Port)	368 (432) ¹	608 (736) ¹	848 (1008) ¹	992 (1152) ¹
Single Line Port / Single Line Telephone	240	480	720	960
KX-DT300/KX-T7600 series Digital Proprietary Telephone	256	512	640	640
Other Digital Proprietary Telephone	128	256	384	512
Analog Proprietary Telephone	80	160	240	320
IP Proprietary Telephone	224	384	544	672
IP Proprietary Telephone ² (supported by IP-EXT16 card)	160	320	480	640
IP Proprietary Telephone ³ (supported by IPCEMPR card)	64			
SIP Extension	128			
DSS Console	64			
Cell Station	32	64	96	128
High-Density Cell Station	16	32	48	64
Multicell Wireless Phone	512			
Voice Processing System (VPS) ⁴	8			
Doorphone	16	32	48	64
Door Opener	16	32	48	64
External Sensor	16	32	48	64
External Relay	16	32	48	64

1 Even when Digital Extra Device Port is used, each shelf supports a maximum of 256 KX-DT300/KX-T7600 series Digital Proprietary Telephones.

2 KX-NT300 series (except KX-NT366/KX-NT305), KX-NT265, and KX-NT136.

3 KX-NT300 series and KX-NT265 (software version 2.00 or later only).

4 Only a single VPS can be connected to one optional service card.



Panasonic Communication Company of North America

Executive Offices:
Three Panasonic Way, Secaucus, NJ 07094
(201) 348-7000

www.panasonic.com/ecs

Panasonic Customer Service

9 am - 9 pm (EST) Mon. through Fri.
10 am - 7 pm (EST) Sat. and Sun.
1-800-211-PANA

www.panasonic.com/support

For hearing or speech impaired TTY users, TTY 1-877-833-8855