

# Panasonic Puts You in Command

Offering many unique combinations of features when a Panasonic Voice Processing System is integrated with a Panasonic Telephone System.

KX-TVA50 and KX-TVA200 Features			
System Features		Subscribers Features	
Alternate Extension Group	Interview Service	Auto Receipt Confirmation	Receive Message
Auto Forwarding	List All Names	Automatic Log-In (APT/DPT Integration Only)	Message Recovery
Automated Attendant	Logical Extension (All Calls Transfer to Mailbox)	Autoplay New Message	Remote Call Forwarding Set (DPT Integration Only)
Broadcasting Messages	Message Delivery, Internal	Bookmark	Subscriber Tutorial
Busy Coverage Mode	Message Reception Mode	Call Transfer Status	Temporary Personal Greeting
Call Transfer to Outside Line	Message Waiting Notification—Device	Callback Number Entry	Timed Reminder Setting (DPT Integration Only)
Caller ID <sup>3</sup> Call Routing (APT/DPT Integration Only)	Message Waiting Notification—Lamp	Caller ID <sup>3</sup> Callback (DPT Integration Only)	Toll Saver (APT/DPT Integration Only)
Caller ID <sup>3</sup> Screening (APT/DPT Integration Only)	Multilingual Service	Calling a Beeper (Pager)	Two-way Record (APT/DPT Integration Only)
Caller Name <sup>3</sup> Announcement – Personal (APT/DPT Integration Only)	No Answer Coverage Mode	Delete Message Confirmation	Two-way Transfer (APT/DPT Integration Only)
Caller Name <sup>3</sup> Announcement – System (APT/DPT Integration Only)	On Hold Announcement Menu	External Message Delivery Service	Unlimited Message Length
Class of Service (COS)	Operator Service	Group Distribution List – Personal	Urgent Message
Company Greeting	PIN Call Routing	Group Distribution List – System	VM Menu (DPT Integration Only)
Company Name	Play System Prompt After Personal Greeting	Incomplete Call Handling Service	
Covering Extension	Port Service	Live Call Screening (APT/DPT Integration Only)	System Setting Features
Custom Service	Rotary Telephone Service	Mailbox Capacity Warning	Auto Configuration (APT/DPT Integration Only)
Daylight Saving Time Assignment	Service Access Commands	Message Transfer	Custom Service Builder
Dial by Name	Service Groups	One-touch Two-way Transfer (DPT Integration Only)	Default Mailbox Template
DID Call Routing (DPT Integration Only)	System Clock	Personal Custom Service	Password Administration
E-mail Integration	System Prompts	Personal Greeting for Caller ID (APT/DPT Integration Only)	Recording by System Administrator
Extension Group	Time Service (day, night, lunch, and break)	Personal Greetings	Service Mode
Fax Management	Trunk Service (Universal Port) (APT/DPT Integration Only)	Playback Volume/Speed Control	System Backup/Restore
Hold	Voice Mail Service	Private Message	System Reports
Holiday Service			System Security
Intercom Paging (APT/DPT Integration Only)			Time Synchronization (DPT Integration Only)
Voice KX-TVA50 and KX-TVA200 Maximum Capacities and Specifications			
		KX-TVA50	KX-TVA200
KX-TVA502	2-Port Hybrid Expansion Card	2	
KX-TVA524	Memory Expansion Card	1	
KX-TVA594	LAN Interface Card	1	
KX-TVA296	Modem Card	1	1
KX-TVA204	4-Port Digital Expansion Card		6
Initial Configuration and Expansion Capabilities			
No. of Ports	Initial Configuration	2	4
	Maximum	6	24
Recording Time	Initial Configuration	4 hours	1000 hours
	Maximum	8 hours	
Specifications			
Custom Services		Up to 100	
Number of Messages		Limited by Storage Time	
Length of Personal Greeting Message		Up to 360s (programmable)	
Message Retention Time		1 to 30 days (programmable)	
Maximum Message Length		1 to 60 minutes (programmable)	
Maximum Combined Length of Message per Mailbox		1 to 600 minutes (programmable)	
Number of Mailboxes		62 Subscriber + 2 Manager	1022 Subscriber + 2 Manager
Power Source		100 V AC to 240 V AC, 0.25 A, 50 Hz/60 Hz	100 V AC to 240 V AC, 1.5A, 50 Hz/60 Hz
DC Input		9 V, 0.75 A (6.75 W)	40 V, 1.38 A (55.2 W)
Dimensions (W x H x D)		9 7/8" (W) x 12 3/8" (H) x 2 7/8" (D)	10 7/8" (W) x 14 7/8" (H) x 4 5/8" (D)
Weight		4.41 lbs	9.7 lbs

- 1 - This brochure describes features that are available when a Panasonic KX-TVA voice processing systems are digitally integrated with a Panasonic Digital Hybrid IP-PBX system. Some features may be available only when the systems are digitally integrated and digital telephones are utilized. See your dealer for details.
- 2 - Must be connected to a PBX that supports Message Waiting Lamp.
- 3 - Requires subscription to Caller ID service offered by certain telephone companies for a fee.

**Panasonic System Networks Company of America**  
 Executive Offices:  
 Three Panasonic Way, Secaucus, NJ 07094  
 (201) 348-7000

**Panasonic Customer Service**  
 9 am - 9 pm (EST) Mon. through Fri.  
 10 am - 7 pm (EST) Sat. and Sun.  
 1-800-211-PANA

[www.panasonic.com/ecs](http://www.panasonic.com/ecs)